BENDUR INDUSTRIAL HARDWARE & COMPONENTS WEBSTORE

PRODUCT DATASHEET

Central quick connector ISB - slot 8 | 7.9x27.5

Article number: BT-020913.02.08.001





View this product online: https://www.bendur.com/uk/central-quick-connector-isb-slot-8-7-9x27-5-bt0209130208001.html

Product details

Profile system	ISB
Slot type	8
Material	Steel
Finish	Zinc plated
HS-code	7318.15.88.90

Description

With this central connector you join two ISB profiles with slot 8 at a right angle. The connector sits in the core of the profile end and pulls the profiles together; the joint stays almost invisible.

Before assembly you drill a blind hole Ø14.2 mm, 28 mm deep, in the side of one profile and a blind hole Ø8.2 mm, 20 mm deep, in the end of the other profile. A cover cap closes the side hole.

- Connector: steel, zinc plated; clamp: stainless steel
- Cover cap: plastic PP, grey (≈ RAL 7042)
- Machining: blind hole Ø14.2 x 28 mm (side) and Ø8.2 x 20 mm (end)
- Electrically conductive (ESD) connection
- For ISB profiles 40 series, slot 8
- Weight: 42.8 g

Bendur B.V.

Vaarselstraat 10a | 5711RE Someren | The Netherlands

Tel. +31 (0)40 340 01 86 | www.bendur.com

This document was automatically generated on 25-11-2026. Subject to change.